



Weighing & Counting Scale

SW-II LED



Weighing & Counting Scale

As a simple weighing scale with a maximum of 1/15,000 resolution, SW-II is suitable in a variety of industrial environments, including traditional market, with its low body and ergonomics design.



Easy Grab Body



Rear Display



USB Port



FEATURE

- High Resolution for Weighing (Max. 1/15,000, Certificate 1/3,000 dual)
- Easy Grab Body
- Ergonomics design with a low body and comfortable handling



- USB Port for COMM. & Power (Option)



- Rear Display for Customer (Option)



- Rechargeable Battery (Option)
- A maximum of 1,000 hours when used with Mn or Pb battery together

OPTION

- RS-232 (Print, Command)
- Rear Display
- Rechargeable Battery & Adaptor
- USB Port
- SUS Tray

APPLICATION

- Open market, Farm, Industrial Environment

SPECIFICATION

| MODEL | SW-II-03 | SW-II-06 | SW-II-15 | SW-II-30 |
|----------------|--|----------------|--------------|--------------|
| Capacity | 3kg | 6kg | 15kg | 30kg |
| e (Non-Certi.) | 0.5g, 0.2g, 0.1g | 1g, 0.5g, 0.2g | 2g, 1g, 0.5g | 5g, 2g, 1g |
| e (Certi.) | 0.5/1(g) Dual | 1/2(g) Dual | 2/5(g) Dual | 5/10(g) Dual |
| Resolution | 1/3,000 ~ 1/15,000 Dual Interval, Certi.(1/3000~1/15,000) | | | |
| Display | 6Digit LED (115x39.5mm) | | | |
| Symbols | STABLE, ZERO, TARE, g, kg, lb, oz, PCS, Low Battery HI / OK / LO & PCS | | | |
| Functions | Hold, Unit Conversion, Counting-Counting SampleRange:10~100, 200, 300, 400, 500 Weight Comparison Function : HI, OK, Low, Sleep Mode Function | | | |
| Operation Time | Approx. D size Battery = 500hr Or Pb Battery = 450hr (Backlight off) Approximately 1,000 hours consecutively when equipped with Mn Battery and Pb Battery altogether | | | |
| Option | RS-232 (Print , Command), Rear Display Rechargeable Battery And Adaptor, USB Port, SUS Tray | | | |
| Power | Mn(500hr), Pb(500hr), Mn+Pb(1000hr) | | | |
| Dimensions | 245 (W) x 280(D) x 110(H) | | | |
| Platter Size | 225(W) x 190 (D) | | | |
| Product Weight | 2.44 kg | | | |

DIMENSION

