

Z-POS Series

“Always right there in front of your payments and transactions”

- The industry's premier point of sale solution for retailers
- Product reliability & safety
- Easy to install and maintain POS systems
- Green IT of low energy consumption



Fan Free, Tool Free Z-POS

The Best hit model Z-POS has the powerful features and smart design.



The Best hit model Z-POS has the powerful features and smart design. Z-POS is two-tone black and white, curved edges for a modern look and focuses on a user-friendly design. The first product in Korea adopts the frame Touch technology and 9.7-inch Dual Monitor option. The I/O (input/output) ports have been placed on the top of the panel, to aid ease of installation and hide cabling. Z-POS has adopted hand-screws to the MSR, HDD and Main Board to further increase ease of installation, servicing and user friendliness.



User Friendly Design

Stylish All-in-one design with 9.7-inch dual monitor



Easy to Service

I/O ports are placed on the top of the panel

Z-POS Series, Stylish POS System

- No Fan, No Noise
- Product reliability & safety
- Easy to install and maintain with Fingertip screws
- Hidden Adapter and cables
- Waterproof and dust resistant LCD panel
- Green IT of low energy consumption

Z-POS

www.cas.co.kr



Z-1500

Normal Touch Type



Z-9000

Frame Touch Type



Product reliability & safety

Proven product reliability and safety through EMC test, KCC, CE & FCC by Authorized Testing and Certification Bodies

Green IT

Intel Atom processor offers low power consumption. Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



Specification

Item	Specification	
Main	Formfactor	170 mm (W) x 170 mm (L) : Mini ITX Platform
	CPU	Onboard Intel Atom Processor Dual Core D2550 (1M Cache, 1.86 GHz)
	Chipset	Intel NM10 Express Chipset
	Memory	DDR3 SODIMM 2GB (up to 4GB by 2 x Slots)
	Storage	2.5" SATA 320GB HDD
Primary Display	LCD	15" TFT, LVDS Interface
	Resolution	1024 x 768
	Touch	15" 5-Wire Analog Resistive Touch (Serial I/F)
Indicator	2 x LEDs and 1 x Buzzer	
Speaker	1 x 1W	
I/O Port	USB	6 ports (2 x Side, 4 x Rear)
	Serial	4 RS-232C ports (3 x Powered DSUB-9, 1 x RJ-45) COM1/4 : 0/5/12V By Jumper, COM2/3 : 0/5/12V By BIOS Select
	PS/2	2 ports (1 x Mouse, 1 x Keyboard)
	LAN	2 Gigabit LAN ports
	VGA	1 VGA port
	Audio	2 ports (1 x Mic-in, 1 x Line-out)
Power	DC-IN	External 60W Adapter
		Input AC 100~240V/ 50~60Hz, Output DC 12V/5A
Software	OS	POSReady2009 / POSReady7
Dimension	W x D x H mm	389 x 206 x 322
Tilt Adjustment	0°~50°	
WEIGHT	6.25kg / 7.47kg (with Dual Monitor)	
User Environment	Temperature	Operating -25 to 65
		Storage -35 to 75

This specification can be changed without Prior notice

ver. ZPOS_201307_EA



1315, Yangjae-daero, Gangdong-gu, Seoul, Korea (134 - 846)
Tel +82-2225-3500, Fax +82-2475-4668, URL www.cas.co.kr

made in Korea