

Thermal Receipt Printer

BTP-301



3" Thermal Receipt Printer

Thermal Receipt printer BTP-301 delivers the quality and reliability of printing result that customers can trust. It is compatible with USB, Serial, Ethernet and provides Parallel, Bluetooth and various options that would bring much stable printing environment.



Metallic Printer Enclosure



Partial Cut



Wide-range of Interfaces



Wall Mounted Kit(Optional)

FEATURE

- High printing speed up to 250mm/s
- Three-in-one interface, including RS232, Ethernet and USB
- Embedded with 2D barcode edition algorithm which supports the 2D barcode common in the market, such as QRcode/ PDF417
- Provide Windows/Linux driver
- Provide complete OPOS driver
- Support page mode printing
- With double cash drawer driver
- Movable paper guard plate design which supports 58mm, 76mm, 80mm wide thermal paper

OPTION

- Interfaces : Parallel, Bluetooth or Wi-Fi
- Wall Mounted Kit

APPLICATION

- Service Counter • Retail • Restaurant • Hotel · Resort



SPECIFICATION

ITEM		BTP-301
Printer	Print method	Direct Thermal Line Printing
	Resolution	Standard 203dpi (8dots/mm), Emulated 180dpi(7dots/mm)
	Print Speed	Max. 250mm/s
	Printing Width	48mm/72mm
Interface	Standard	USB+Serial+Ethernet
	Optional	Parallel, Bluetooth or Wi-Fi
Page Mode		Support
Memory	RAM	16Mb
	Flash	32Mb
Fonts	Chinese	GBK 24×24dots
	Alphanumeric	ASCII 9×17, 12×24dots
	User-defined	YES
	Codepage	48
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	PDF417, QR code
Graphics		Support bitmap printing with different density and user define bitmap printing. (Max size of each bitmap is 40k, the total size of bitmap is 256k)
Detection	Sensors	Paper out detection, cover open detection
LED Indicator	Power	Green LED
	Paper	Red LED
	Error	Red LED
Reliability	TPH life	150km
	Cutter life	1.5 million cuts

