

Bench Scale

BW-1N SERIES



Bench Scale

BW Series has a pivot-type indicator that can be tilted up&down or left or right.

With IP65 Rating the BW series is ideal for wet areas. Like most bench scales the BW series is designed for rough industrial conditions.

Equipped with a counting function. High quality and efficient in warehouses, incoming goods or shipping departments.

Built to stand up to tough treatment like jolt, vibrat



Feature

- Battery operation (dry battery or optional rechargeable battery)
- Low battery indication
- Counting function
- Check weight function (LOW/OK/HIGH)
- On/Off, zero/mode, tare, net/gross, hold (or kg/lb)
- Easy-to-Read, 24 mm, 6 digit LCD display
- Single pass automatic span calibration
- Auto zero tracking
- AC adaptor(DC 12V 1.25A)
- Backlight display


Options

- Rechargeable battery pack
- Wall mount kit
- RS-232C interface



Wall mount kit

Swivel&Tilttable head design



Tilt up-down, 90° (Max.)



Turn left-right, 360° (Max.)

Application



Low cap. Platform



High cap. Platform

Specification

Model	BW Series				
Max.Capacity(kg)	6	15	30	60	150
Interval (g)	2	5	10	20	50
Platter Size (mm)	280(W) x 280(D) x 80(H)			400(W) x 525(D) x 105(D)	
Product Size (mm)	280(W) x 350(D) x 530(H)			425(W) x 675(D) x 755(D)	
Product Weight (kg)	About 6			About 17	
Charge Time	About 6 hr				
Function	General	ON/OFF, Zero, Net, Hold, PCS, RS232, HI, LO, Compare			
	Option	Backlight			
Operatint Temp	-10 °C ~ +40 °C				
Tare	Max Capacity				
Display	6 Digit LCD(24 mm Height) Stable (⊙), Zero (⇒0⇒), Tare (<Δ), Net (NET), Hold (HOLD), Low battery (⊖), Weight unit (kg), High, OK, Low (H, O.K., L), Count (PCB)				
Power (Option.)	1. DC 7.2 V(6 EA SIZE " AA ") 2500 mAh Rechargeable battery 2. DC 9 V(6 EA SIZE " C ") Dry Battery 3. DC 12 V 1.25 A AC Adaptor				
Power consumption	approx. 0.25 W				

Dimension

